



GET IN TOUCH

Contact Number• +91-7400151886

Email Id info@melanasolar.com





Low-power Solar Camera Series

Model MLS-4GS12 MLS-WS12 4G/Wifi Solar Powered Battery Camera & PTZ camera

- 1. 3MP 4G camera built-in 4G module, different modules in different countries
- 2. Pan&Tilt: Pan 355 degree& Tilt 100 degree
- 3. 8 watt solar panel, built-in 15600mAh 6 pcs 18650 batteries
- 4. Two-way voice intercom, IP66 Waterproof
- 5. Cloud storage and TF card storage maximum 128G(without TF card)
- 4G network remote viewing/playback via APP (UBox)
 WIFI 2.4GHz , IEEE 802.11 b/g/n, remote viewing/playback via APP(UBox)
- 7. Automatic video recording and message push when human body motion wakes up
- 8. 3.6mm lens, built-in infrared light + white light, night vision full color or infrared mode optional
- 9. Infrared distance 15 meters. Arbitrary arming time can be set



Model MLS-4GS12-10X MLS-WS12-10X 4G/Wifi Solar 10x Optical Zoom Camera

- 1. 5MP 4G/Wifi solar powered battery PTZ camera
- 2. Pan&Tilt:Pan 355 degree&Tilt 100 degree
- 3. 8 watt solar panel, built-in 15600mAh 6 pcs 18650 batteries
- 4. Two-way voice intercom
- 5. Cloud storage and TF card storage maximum 128G (without TF card)
- 6. WIFI Camera: WIFI 2.4GHz, IEEE 802.11 b/g/n, remote viewing/playback via APP (UBox)
- 4G Camera: Built-in 4G module, different modules in different countries.
- 4G networkremote viewing/playback via APP (UBox)
- 7. Automatic video recording and message push when human body motion wakes up
- 8. Arbitrary arming time can be set
- 5-50mm 10x optical zoom lens, built-in infrared light + white light, night vision full color or infrared mode optional IR distance 40 meters
- Waterproof grade IP66



Main Feature




























Model MLS-4GS20L MLS-WS20L

4G/Wifi Dual Lens Dual PIR Solar Powered Battery Camera

- 1. 6MP dual lens wifi solar powered battery floodlight PTZ camera
- 2. Pan&Tilt:Pan 355 degree&Tilt 100 degree
- 3. 9 watt solar panel with 3m extension cord, built-in 15600mAh batteries
- 4. Two-way voice intercom
- 5. Cloud storage and TF card storage maximum 128G (without TF card)
- 6. Dual PIR +Ai humanoid detection alarm and video recording
- 7. Arbitrary arming time can be set
- 8. 2.8mm +6mm lens,built-in infrared light + white light, night vision full color or infrared mode optional, IR distance 30 meters
- 9. Support dual-video linkage positioning and humanoid automatic tracking
- 10. Waterproof grade IP66
- 11. 4G Camera: Built-in 4G module, different modules in different countries.4G network remote viewing/playback via APP (UBox).

WIFI Camera: WIFI 2.4GHz, IEEE 802.11 b/g/n, remote viewing/playback via APP (UBox).









Two-way Voice





PTZ Rotation

Color Night Vision

Motion Detection



Alarm Push







SD Card Storage 3m Extension Line









Model MLS-WS20L-20X MLS-4GS20L-20X

4G/Wifi Dual Lens Dual PIR 20X Zoom Solar Powered Battery Camera

- 1. 6MP dual lens wifi/4G solar powered battery floodlight PTZ camera
- 2. Pan&Tilt: Pan 355 degree&Tilt 100 degree
- 3. 9 watt solar panel with 3m extension cord, built-in 10400mAh batteries
- 4. Two-way voice intercom
- 5. Cloud storage and TF card storage maximum 128G (without TF card)
- 6. 4G Camera: Built-in 4G module, different modules in different countries.4G network remote viewing/playback via APP (UBox).

WIFI Camera: WIFI 2.4GHz, IEEE 802.11 b/g/n, remote viewing/playback via APP (UBox).

- 7. Supports Bluetooth quick network configuration
- 8. Dual PIR +Ai humanoid detection alarm and video recording
- 9. Arbitrary arming time can be set
- 10. 2.8mm wide-angle lens + 5-50mm 20x zoom PTZ lens, Seeing clearly from far and near
- 11. Built-in infrared light + white light, night vision full color or infrared mode optional, IR distance 40 meters
- 12. Support dual-video linkage positioning and humanoid automatic tracking
- 13. Waterproof grade IP66






Model MLS-4GS40 MLS-WS40 3MP 4G/Wifi Solar Camera 24-hour Recording

- 1. 24-hours long video + low power sleep dual mode wifi solar powered battery PTZ camera
- 2. 24-hour recording when the battery is sufficient, trigger recording when the battery is low
- 3. Pan&Tilt:Pan 355 degree&Tilt 100 degree
- 4. 20 watt solar panel, built-in 30000mAh batteries 5. Two-way voice intercom
- 6. Cloud storage and TF card storage maximum 128G (without TF card)
- 7. WIFI Camera: WIFI 2.4GHz, IEEE 802.11 b/g/n, remote viewing/playback via APP (UBox)
- 4G Camera: Built-in 4G module, different modules in different countries.
- 4G networkremote viewing/playback via APP (UBox)
- 8. Mobile phone APP message push when someone is detected
- 9. Arbitrary arming time can be set
- 3.6mm lens,built-in infrared light + white light, night vision full color or infrared mode optional IR distance 15 meters
- 11. Waterproof grade IP66









Spliced Solar Panel

The packaging volume is small, the transportation is convenient, and the installation is simple.









Model MLS-4GS40-20X MLS-WS40-20X 5MP 4G/Wifi Solar Camera 24-hour Recording

- 1. 24-hours long video + low power sleep dual mode wifi solar powered battery PTZ camera
- 2. 24-hour recording when the battery is sufficient, trigger recording when the battery is low
- 3. Pan&Tilt:Pan 355 degree&Tilt 100 degree
- 4. 20 watt solar panel, built-in 30000mAh batteries 5. Two-way voice intercom
- 6. Cloud storage and TF card storage maximum 128G (without TF card)
- 7. WIFI Camera: WIFI 2.4GHz, IEEE 802.11 b/g/n, remote viewing/playback via APP (UBox)
- 4G Camera: Built-in 4G module, different modules in different countries.
- 4G networkremote viewing/playback via APP (UBox)
- 8. Mobile phone APP message push when someone is detected
- 9. Arbitrary arming time can be set
- 10. 5-50mm 20x zoom lens, built-in infrared light + white light, night vision full color or infrared mode optional IR distance 40 meters
- 11. Waterproof grade IP66












Model MLS-MS1-4G MLS-MS1 4K Dual Lens 4G/Wifi Solar Powered Camera

- 1. 4K dual lens solar powered battery floodlight PTZ camera
- 2. Wifi Model: WIFI 2.4GHz, IEEE 802.11 b/g/n. 4G Model: Built-in 4G module, different modules in different countries
- 3. Pan&Tilt:Pan 355 degree&Tilt 90 degree
- 4. 9 watt solar panel with 2m extension cord, built-in 20000mAh batteries
- 5. Cloud storage and TF card storage maximum 128G (without TF card)
- 6. Support Android, IOS APP remote viewing/playback (APP:NiView)
- 7.PIR + humanoid detection wake-up video recording and message push.Two-way voice intercom.
- 8. 24 hours recording, 24 hours + trigger recording, trigger recording three working modes
- 9.2.5mm wide-angle lens + 6mm lens, Seeing clearly from far and near
- 10.Built-in infrared light + white light, night vision full color or infrared mode optional IR distance 40 meters
- 11. Support motion detection, humanoid detection, dual-video linkage positioning and humanoid automatic tracking
- 12. Waterproof grade IP66. Optional: For \$20 more, choose an extra 6-watt solar panel (LS-MS1-S)





Model MLS-MS2-4G MLS-MS2 4K Dual Lens 180° Ultra Wide Angle Solar Camera


- 1. 4K/8MP WIFI/4G panoramic solar powered battery camera;
- Dual lens 180° ultra wide Angle monitoring;
- Wifi Model: WIFI 2.4GHz , IEEE 802.11 b/g/n.
 4G Model: Built-in 4G module, different modules in different countries
- 4. 6 watt solar panel with 2m extension cord, built-in 18000mAh batteries, solar panels support integrated installation and separate installation
- 5. Two-way voice intercom
- 6. Cloud storage and TF card storage maximum 128G (without TF card)
- 7. Support Android, IOS APP remote viewing/playback (APP:NiView)
- 8.PIR + humanoid detection wake-up video recording and message push
- 9. 24 hours recording, 24 hours + trigger recording, trigger recording three working m
- 10.Built-in infrared light + white light, night vision full color or infrared mode optional
- IR distance 15 meters
- 11.2pcs 2.8mm lenses spliced to super wide angle viewing, 4x digital zoom and dual channel preview to achieve a panoramic and detailed view.
- 12. Support humanoid detection, humanoid automatic tracking,
- 13. Waterproof grade IP66



















Model MLS-MS3A-10X MLS-MS3A-4G-10X Multi-Lens 4G/Wifi Solar Battery Camera

- 1. WiFi Version Camera:
- (1). 2K/ 4MP multi-lens wifi solar powered battery floodlight PTZ camera
- (2). WIFI 2.4GHz, IEEE 802.11 b/g/n;
- 2. 4G Version Camera:
- (1). 2K/ 4MP multi-lens 4G & wifi solar powered battery floodlight PTZ camera
- (2). Support 4G and wifi 2.4GHz two modes of Internet access,

through the mode switch change


- 3. Pan&Tilt:Pan 355 degree&Tilt 90 degree
- 4. 6 watt solar panel with 2m extension cord, built-in 12000mAh batteries
- 5. Two-way voice intercom
- 6. Cloud storage and TF card storage maximum 128G (without TF card)
- 7. Support Android, IOS APP remote viewing/playback (APP:NiView)
- 8.PIR + humanoid detection wake-up video recording and message push
- 9. 24 hours recording, 24 hours + trigger recording, trigger recording three working modes
- 10.2.8mm wide-angle lens and 6mm+16mm PTZ lens,10X Optical + Digital Hybrid zoom,Seeing clearly from far and near
- 11.Built-in infrared light + white light, night vision full color or infrared mode optional IR distance 25 meters
- 12. Support motion detection, humanoid detection, dual-video linkage positioning and humanoid automatic tracking
- 13. Waterproof grade IP66

















Model MLS-4GS21M MLS-WS21 4G/Wifi Solar Battery Camera

- 6MP dual lens wifi solar powered battery floodlight PTZ camera
- 2. Pan&Tilt:Pan 355 degree&Tilt 100 degree
- WIFI Camera: 6 watt solar panel with 3m extension cord, built-in 10000mAh batteries
 4G Camera: 6 watt solar panel with 3m extension cord, built-in 15000mAh batteries
- 4. Two-way voice intercom
- 5. Cloud storage and TF card storage maximum 128G (without TF card)
- WIFI Camera: WIFI 2.4GHz , IEEE 802.11 b/g/n, remote viewing/playback via APP(UBox)
 4G Camera: 4G network remote viewing/playback via APP (UBox)
- 7. Dual PIR +Ai humanoid detection alarm and video recording
- 8. Arbitrary arming time can be set
- 2.8mm +6mm lens,built-in infrared light + white light, night vision full color or infrared mode optional, IR distance 30 meters
- 10. Support dual-video linkage positioning and humanoid automatic tracking
- 11. Waterproof grade IP66














Model MLS-4GS16M 4G Solar Powered Battery Camera & PTZ camera

- 1. 3MP 4G solar powered battery PTZ camera
- 2. Built-in 4G module, different modules in different countries
- 3. Pan&Tilt:Pan 240 degree&Tilt 100 degree
- 4. 6 watt solar panel with 3m extension cord, built-in 10400mAh batteries
- 5. Two-way voice intercom
- 6. Cloud storage and TF card storage maximum 128G (without TF card)
- 7. 4G network remote viewing/playback via APP (UBox)
- 8. Automatic video recording and message push when human body motion wakes up
- 9. Arbitrary arming time can be set
- 10.3.6mm lens, built-in infrared light + white light, night vision full color or infrared mode optional IR distance 15 meters
- 11. Waterproof grade IP66




























- 1. 4G solar alert intelligent hunting camera
- 2. Built-in 4G module, different modules in different countries
- 3. 4 watt solar panel with 3m extension cord, built-in 7800mAh (18650) batteries, supports quick disassembly and replacement

Clearly capture the moment of wildlife

- 4. Two-way voice intercom
- 5. Cloud storage and TF card storage maximum 128G (without TF card)
- 6. 4G network remote viewing/playback via APP (UCon)
- 7. Ultra-low power standby, quick wake up in 0.2 seconds
- 8. PIR sensing +Ai move detection alarm
- 9. Support picture mode (14MP) or video mode(4MP) can be set
- 10. 3.6mm lens, built-in infrared light (850nm), night vision distance 15 meters
- 11. Support integrated installation and separated installation
- 12. Waterproof grade IP66














Model MLS-WS10M 3MP HD 4G/WIFI Solar Battery Camera

- 1. 4G/WIFI solar powered battery PTZ camera
- 3. Pan&Tilt:Pan 240 degree&Tilt 100 degree
- 4. WIFI Camera: 3.5 watt solar panel with 3m extension cord, built-in 7800mAh batteries
 4G Camera: 6 watt solar panel with 3m extension cord, built-in 7800mAh batteries
- 5. Two-way voice intercom
- 6. Cloud storage and TF card storage maximum 128G (without TF card)
- WIFI Camera: WIFI 2.4GHz , IEEE 802.11 b/g/n, remote viewing/playback via APP(UBox)
 4G Camera: Built-in 4G module, different modules in different countries, 4G network
 remote viewing/playback via APP(UBox)
- 8. Automatic video recording and message push when human body motion wakes up
- 9. Alarm deployment time can be set
- 3.6mm lens,built-in infrared light + white light, night vision full color or infrared mode optional IR distance 15 meters
- 11. Waterproof grade IP66











Model MLS-WS17M 3MP HD 4G/WIFI Solar Battery Camera

- 1. 4G/WIFI solar powered battery PTZ camera
- 3. Pan&Tilt:Pan 240 degree&Tilt 100 degree
- 4. WIFI Camera: 3.5 watt solar panel with 3m extension cord, built-in 7800mAh batteries
 4G Camera: 6 watt solar panel with 3m extension cord, built-in 7800mAh batteries
- 5. Two-way voice intercom
- 6. Cloud storage and TF card storage maximum 128G (without TF card)
- WIFI Camera: WIFI 2.4GHz , IEEE 802.11 b/g/n, remote viewing/playback via APP(UBox)
 4G Camera: Built-in 4G module, different modules in different countries, 4G network remote viewing/playback via APP(UBox)
- 8. Automatic video recording and message push when human body motion wakes up
- 9. Alarm deployment time can be set
- 3.6mm lens,built-in infrared light + white light, night vision full color or infrared mode optional IR distance 15 meters
- 11. Waterproof grade IP66





Two Night Vision Modes

Default whitelight offers color night vision, and IR LED offers black/white night vision,

you can easily change in live view page on app.













MLS-WS10 MLS-4GS10 3.5W

3MP 4G/Wifi solar powered battery camera & PTZ camera

- Wifi Model: WIFI 2.4GHz , IEEE 802.11 b/g/n,built-in 7800mAh batteries.
 4G Model: Built-in 4G module, different modules in different countries, built-in 10400mAh batteries
- 2. Pan&Tilt:Pan 355 degree&Tilt 100 degree
- 3. 3.5 watt solar panel
- 4. Two-way voice intercom
- 5. Cloud storage and TF card storage maximum 128G (without TF card)
- 6. Remote viewing/playback via APP (UBox)
- 7. Automatic video recording and message push when human body motion wakes up
- 8. Arbitrary arming time can be set
- 9. 3.6mm lens,built-in infrared light + white light, night vision full color or infrared mode optional IR distance 15 meters
- 10. Waterproof grade IP66



MLS-WS14 MLS-4GS14 3.5W/6W

3MP 4G/Wifi solar powered battery camera & PTZ camera

- 1. Wifi Model: WIFI 2.4GHz , IEEE 802.11 b/g/n,
- 4G Model: Built-in 4G module, different modules in different countries
- 2. Pan&Tilt:Pan 355 degree&Tilt 100 degree
- Wifi Model: 3.5 watt solar panel, built-in 7800mAh batteries.
- 4G Model: 6 watt solar panel, built-in 10400mAh batteries
- 4. Two-way voice intercom
- 5. Cloud storage and TF card storage maximum 128G (without TF card)
- 6. Remote viewing/playback via APP (UBox)
- 7. Automatic video recording and message push when human body motion wakes up
- 8. Arbitrary arming time can be set
- 9. 3.6mm lens, infrared light or white light can be set, dual use for video surveillance and garden lights
- 10. Waterproof grade IP66

MELANAS GREEN ENERCY JOURIONS This

Application Scenario



Doorway

Reservoir



Villa

Orchard





Street



Construction Site





Model MLS-CS3 V380 Pro 4G/WIFI Solar Battery Camera

- 1. 2K dual-lens dual-screen wifi/4G solar powered battery PTZ camera
- 2. Pan&Tilt:Pan 355 degree&Tilt 100 degree
- 3. 8 watt solar panel with 1.8m extension cord, built-in 8000mAh batteries
- 4. Two-way voice intercom
- 5. Cloud storage and TF card storage maximum 128G (without TF card)
- 6. WIFI Camera: WIFI 2.4GHz , IEEE 802.11 b/g/n, remote viewing/playback via APP (V380 Pro)
 - 4G Camera: 4G network, remote viewing/playback via APP (V380 Pro)
- 7. PIR +Ai humanoid detection alarm and video recording
- 8. Arbitrary arming time can be set and alarm sound can be set
- 9. 3.6mm +3.6mm lens, built-in infrared light + white light, IR distance 20 meters
- 10. Support humanoid automatic tracking
- 11. Waterproof grade IP66







Model MLS-CS9 AOV 4G/WIFI Solar Battery Camera (24/7 Video Recording)

- 1. 2K dual-lens dual-screen wifi/4G solar powered battery PTZ camera
- Pan&Tilt:Pan 355 degree&Tilt 100 degree
- 3. 8 watt solar panel with 1.8m extension cord, built-in 10400mAh batteries
- 4. Two-way voice intercom
- WIFI Camera: Cloud storage and TF card storage maximum 128G (without TF card)
 4G Camera: TF card storage maximum 128G (without TF card)
- WIFI Camera: WIFI 2.4GHz , IEEE 802.11 b/g/n, remote viewing/playback via APP (Hisee X)
 4G Camera: 4G network, remote viewing/playback via APP (Hisee X)
- 7. Supports Bluetooth quick network configuration
- 8. Al humanoid detection/motion detection alarm push
- 9. 7*24 hours condensed video recording recording Keep the battery camera constantly working
- Always on video (AOV), standby low frame recording, motion detection
 /humanoid detection full frame recording
- 11. 4mm +4mm lens, built-in infrared light + white light, IR distance 20 meters
- 12. Waterproof grade IP66





Multi Lens Camera Series

Model MLS-WL342-10X LS-WL342-20X 10X/20X Zoom Linkage WIFI PTZ camera


- 1. Four 4MP ultra high definition lenses, linked alarm WIFI cameras;
- 2. 3.5-inch engineering plastic shell, outdoor waterproof;
- 3. Four lenses and three frames, horizontal dual shot ultra wide angle+10x zoom lens for panoramic and detail free surveillance Control:
- 4. Efficient monitoring, one top three (2 gun machines+1 billiards machine);
- 5. Built-in infrared and white light, night vision infrared and night vision full color options;
- 6. Pan tilt rotation angle: 0-355 degrees horizontally and 0-90 degrees vertically;
- 7. Multiple networking methods using 2.4G WIFI and RJ45 network ports;
- 8. Support TF storage and cloud storage;
- 9. Dual voice intercom, dual video synchronous recording and playback
- 10. Human shape detection/vehicle detection/pet detection/other detection

(you need to pay to open it, and then open Cloud storage Can)

- Automatic tracking/movement alarm, alarm output, sound and light linkage;
- 12. Al intelligent algorithm to achieve 3D positioning of gun ball videos and continuous tracking of target alarms;
- 13. Support remote management of Android/Apple mobile apps (IPC360 Home)














Model MLS-WL341-10X 10X Optical Zoom Linkage WIFI PTZ camera

- 1. 3.5 inch 4MP HD 10x zoom PTZ camera;
- Three-lens dual-screen, ultra-wide-angle + 10x zoom to achieve clear monitoring from far and near;
- Dual light source design, built-in infrared light + white light, night vision infrared and night vision full color can be set;
- Pan&Tilt: horizontal 0~355 degrees, vertical 0~90 degrees;
- 2.4G WIFI + RJ45 network port for Internet access;
- Support TF storage and cloud storage (free one month cloud storage);
- 7. Two-way voice intercom, two-way video synchronous recording and playback
- 8. Humanoid detection/vehicle detection/pet detection/other detection (need to open cloud storage)
- 9. Automatic tracking/movement alarm, alarm output sound and light linkage;
- 10. Al intelligent algorithm to achieve video 3D positioning and continuous tracking of target alarms;
- 11. Support Android/IOS APP remote management (IPC360 Home).
- 12. power supply DC 12V







Model MLS-WL341-20X 20X Optical Zoom Linkage WIFI PTZ camera

- 1. 3.5 inch 4MP HD 20x zoom PTZ camera;
- Four-lens dual-screen, ultra-wide-angle + 20x zoom PTZ to achieve clear monitoring from far and near;
- Dual light source design, built-in infrared light + white light, night vision infrared and night vision full color can be set;
- Pan&Tilt: horizontal 0~355 degrees, vertical 0~90 degrees;
- 5. 2.4G WIFI + RJ45 network port for Internet access;
- 6. Support TF storage and cloud storage (free one month cloud storage);
- 7. Two-way voice intercom, two-way video synchronous recording and playback
- 8. Humanoid detection/vehicle detection/pet detection/other detection (need to open cloud storage)
- 9. Automatic tracking/movement alarm, alarm output sound and light linkage;
- 10. Al intelligent algorithm to achieve video 3D positioning and continuous tracking of target alarms;
- 11. Support Android/IOS APP remote management (IPC360 Home).
- 12. power supply DC 12V





Model MLS-WL350-10X Three Screen Wifi 10X Zoom PTZ Camera

- 1. 3.5 inch 12MP HD PTZ camera;
- 2. Four-lens three-screen, 10X zoom 360-degree surveillance;
- 3. Dual light source design, built-in infrared light + white light,

4. Pan&Tilt: horizontal 0~355 degrees, vertical 0~90 degrees;

- night vision infrared and night vision full color can be set;
- 5. Two bullet cameras support horizontal and vertical 180 degrees manual arbitrary adjustment
- 6. 2.4G WIFI + RJ45 network port for Internet access;
- 7. Support TF storage and cloud storage;
- 8. Two-way voice intercom, three-way video synchronous recording and playback;
- 9. Support motion detection, intelligent alarm;
- 10. Support automatic tracking;
- 11. Support Android/IOS APP remote management;
- 12. power supply DC 12V



Model MLS-WL351-10X Four Screen Wifi 10X Zoom PTZ Camera

- 1. 3.5 inch 8MP HD PTZ camera;
- 2. Five-lens four-screen, 10X zoom 360-degree surveillance;
- Dual light source design, built-in infrared light + white light, night vision infrared and night vision full color can be set;
- 4. Pan&Tilt: horizontal 0~355 degrees, vertical 0~90 degrees;
- 5. Two bullet cameras support horizontal and vertical 180 degrees manual arbitrary adjustment
- 2.4G WIFI + RJ45 network port for Internet access;
- 7. Support TF storage and cloud storage;
- 8. Two-way voice intercom, four-way video synchronous recording and playback;
- 9. Support motion detection, intelligent alarm;
- Support automatic tracking;
- Support Android/IOS APP remote management;
- 12. power supply DC 12V




















Model MLS-WL560-36X 36X Optical Zoom WIFI PTZ Camera

- 1. 4.5 inch 6MP HD 36X zoom PTZ camera:
- 2. Dual-lens dual-screen, ultra-wide-angle + 36X optical zoom PTZ to achieve clear monitoring from far and near;
- 3. Dual light source design, built-in infrared light + white light, night vision infrared and night vision full color can be set;
- 4. Pan&Tilt: horizontal 0~355 degrees, vertical 0~90 degrees;
- 5. 2.4G WIFI + RJ45 network port for Internet access;
- 6. Support TF storage and cloud storage (free one month cloud storage);
- 7. Two-way voice intercom, two-way video synchronous recording and playback;
- 8. Support humanoid detection, motion detection, intelligent sound and light alarm;
- 9. Support ONVIF protocol and access NVR;
- 10. Supports PC client preview (VMS);
- 11. Support Android/IOS APP remote management;
- 12. power supply DC 12V.


















Model MLS-P550-30X LS-P550-4G-30X 5MP 30X Optical Zoom 4G/WIFI PTZ camera

- 1. 4.5 inch 5MP HD WIFI/4G PTZ camera;
- 2. Metal+ plastic case, outdoor waterproof;
- 3. Rotation Angle: 355 degrees horizontal, 90 degrees vertical, the highest speed of 60 degrees /S;
- 4. WIFI/4G antenna, TF card storage, cloud storage, two-way voice intercom;
- 5. 30X optical zoom lens, the maximum daytime viewing distance of 1000-2000 meters;
- 6. Dual light source design, night vision full color 50 meters, night vision infrared 120 meters;
- 7. Support humanoid detection, sound and light alarm, APP push, and custom alarm sound
- 8. Support humanoid tracking, and automatically zoom the lens in the tracking process;
- 9. Support preset points and cruise function;
- 10. Support ONVIF protocol and access NVR;

Support Android /IOS APP


and PC Client Manag

- 11. Support 2.4G WIFI/4G SIM Card and RJ45 access network;
- 12. Support Android/IOS APP and PC client management (APP CamHipro)





MELANA





Al High-speed Dome Cameras Series

- 1. Forest fire source detection and thermal imaging function (limited to visible light+thermal imaging cameras)
- 2. Intelligent Video Analysis:

Area Intrusion、Line Crossing、Region Exit、Wandering Detection、Personnel Gathering Detection、


Quick Motion Detection Audio Exception Detection

- 3. PTZ function: 3D Zoom ,Preset , Cruise ,Synchronized scanning, Linear Sweep, Circular scan,PT position automatic correction
- 4. Pan Range: 360° (Endless). Pan Speed: Manual Speed 0.1°-200°/sec (preset 0.1°-250°/sec)
- 5. Tilt Range: 100° (-10~90°). Tilt Speed: Manual Speed 0.5°-100°/sec (preset 0.1°-120°/sec)
- 6. Infrared distance: 200m/500m/800m
- 7. Micro SD (Up to 256GB)
- 8. Alarm in / out , Audio in / out
- 9. Mechanical Wiper
- 10. Day and night (ICR)
- 11. Supports ONVIF
- 12. WDR
- 13. Electronic image stabilization (EIS)
- 14. IP66 waterproof, IK10 explosion-proof
- 15. Power supply: AC24v2A
- 16.PoE (Optional)

Default is standard wall mounting bracket, optional pendant mounting bracket



PRODUCT ADVANTAGES














High-speed Dome Cameras(Visible)

	MELANAF			MELANA			MELANA		
Pixels	2MP	4MP	8MP	2MP	4MP	8MP	4MP	4MP	8MP
Optical Zoom	44X	32X	37X	44X	32X	37X	25X	32X	20X
IR Distance		200m			800m			500m	

High-speed Dome Cameras(Visible+Thermal)

	ME	ANA	MELANA			
Pixels	4MP	4MP	4MP	4MP		
Optical Zoom	37X	37X	25X	32X		
Thermal	384*256 50mm lens	640*512 50mm lens	384*256 25mm lens	640*512 25mm lens		
Thermal Imaging Visual Distance	100	00m	1000m			
IR Distance	20	0m	80m			












APPLICATION SCENARIOS






















- Support Six Al alert functions: Area Intrusion, Line-Cross Detection, Loitering, Absent Alarm,
 Vehicle illegal Parking, Vehicle Retrograde
- 2. Support mobile APP alarm push
- 3. Support two-way voice intercom
- 4. Modify the night vision mode and camera parameters
- 5. Support custom alarm sound
- 6. Support ordinary event alarm: motion detection, video loss, video occlusion
- 7. Supports mobile APP and PC client management







Vehicle Retrograde



MLS-PK3404 4MP/8MP

- 4 pcs 4MP AI alert POE bullet cameras,
 built-in microphone and speaker, 4mm lens.
- 1 pcs 4CH POE NVR,1 HDD,1 CH 3.5 audio input and
 1 CH 3.5 audio output, VGA and HDMI output
- 3. 25 meter cable*2, 15 meter cable*2, power supply*1, mouse*1





MLS-PK3404H 4MP/8MP

- 1. 2 pcs 4MP AI alert POE bullet cameras
- +2 pcs 4MP Al alert POE dome (Plastic case) cameras, built-in microphone and speaker, 4mm lens
- 1 pcs 4CH POE NVR,1 HDD,1 CH 3.5 audio input and
 1 CH 3.5 audio output, VGA and HDMI output
- 3. 25 meter cable*2, 15 meter cable*2, power supply*1, mouse*1





MLS-PK3408 4MP/8MP


8 pcs 4MP AI alert POE bullet cameras,
 built-in microphone and speaker, 4mm lens
 1 pcs 8CH POE NVR,1 HDD,1 CH 3.5 audio input
 and 1 CH 3.5 audio output, VGA and HDMI output
 25 meter cable*4, 15 meter cable*4,
 power supply*1, mouse*1





MLS-PK3408H 4MP/8MP

- 1. 4 pcs 4MP AI alert POE bullet cameras
- + 4 pcs 4MP Al alert POE dome (Plastic case) cameras, built-in microphone and speaker, 4mm lens
- 2. 1 pcs 8CH POE NVR,1 HDD,1 CH 3.5 audio input and 1 CH 3.5 audio output, VGA and HDMI output
- 3. 25 meter cable*4, 15 meter cable*4, power supply*1, mouse*1




Vehicle illegal Parking






Feature MATE Series IP Camera

- 1. HD network camera, fixed focus, electric zoom lens optional. 2MP,4MP,5MP,6MP,8MP optional.
- 2. H.265, H.264, dual stream.ONVIF protocol
- 3. Built-in microphone and speaker ,Two-way voice intercom
- 4. With humanoid detection and alarm function
- 5. Dual light source, support full color night vision and infrared night vision
- 6. IP66 waterproof: adapt to any weather changes outdoors
- 7. The smart series has the functions of six Al alert functions: Area Intrusion, Line-Cross Detection, Loitering, Absent Alarm, Vehicle illegal Parking、Vehicle Retrograde (support access to MATE series NVR linkage application)
- 8. DC12V&POE, IR distance up to 20M/40M











Application Scenario







Residential Area

Garden

Parking Lot

Street










School


Shopping Mall


Airport

Station

CMS Interface







Electronic fence settings

Absent detect settings

Retrograde detect settings







Real-time preview monitoring

HD quality during the day

Infrared or full color night vision

Absent Detect Retrograde Detect

Electronic Fence



MATE Series Ordinary Model



5MP

2. Standard Fixed lens 3.6mm

MLS-MB40501

- H.265, H.264, ONVIF protocol
- 4. Dual light source, support full color night vision and infrared night vision
- 5. Built-in microphone and speaker,

Two-way voice intercom, Humanoid detection

6. DC12V&POE, IR distance up to 20M

(2MP, 5MP, 8MP optional)

MELANAL



- 1. 8MP(3840*2160)15fps;5MP(2592*1944) 25fps
- 2. Standard Fixed lens 3.6mm
- 3. H.265, H.264, ONVIF protocol
- 4. Dual light source, support full color night vision and infrared night vision
- 5. Built-in microphone and speaker,

Two-way voice intercom, Humanoid detection

6. DC12V&POE, IR distance up to 20M

(2MP, 5MP, 8MP optional)

MLS-MD41201 2MP

- 1. 3MP@20fps /2MP@25fps
- 2. Standard Fixed lens 3.6mm
- 3. H.265, H.264, ONVIF protocol
- 4. Dual light source, support full color night vision and infrared night vision
- 5. Built-in microphone and speaker,

Two-way voice intercom, humanoid detection

6. DC12V&POE, IR distance up to 20M

(2MP, 5MP, 8MP optional)

MLS-MD45201 2MP

- 1. 3MP@20fps /2MP@25fps
- 2. Standard Fixed lens 3.6mm
- 3. H.265, H.264, ONVIF protocol
- 4. Built-in infrared light, support infrared night vision
- 5. Built-in microphone and speaker,

Two-way voice intercom, humanoid detection

6. DC12V&POE, IR distance up to 20M

(2MP, 5MP, 8MP optional)

MELANA

1. 3MP@20fps /2MP@25fps

MLS-MB44201M 2MP

- Standard Motorized lens 2.8-12mm
- H.265, H.264, ONVIF protocol
- 4. Dual light source, support full color night vision and infrared night vision
- 5. Built-in microphone and speaker,

Two-way voice intercom, Humanoid detection

6. DC12V&POE, IR distance up to 40M

(2MP, 5MP, 8MP optional)

MLS-MB46501M 5MP

- 5MP@25fps/ 4MP@25fps/ 3MP@25fps /2MP@25fps
- 2. Standard Motorized lens 2.8-12mm
- H.265, H.264, ONVIF protocol
- Dual light source, support full color night vision and infrared night vision

DC12V&POE, IR distance up to 40M

(2MP, 5MP, 8MP optional)



- Built-in microphone and speaker ,

Two-way voice intercom, Humanoid detection

MLS-MD13801M 8MP

- 1. 8MP(3840*2160)15fps; 5MP(2592*1944) 25fps
- 2. Standard Motorized lens 2.8-12mm
- 3. H.265, H.264, ONVIF protocol
- Built-in infrared light, support infrared night vision
- 5. Support humanoid detection
- DC12V&POE, IR distance up to 40M

(2MP, 5MP, 8MP optional)

MATE Series Smart Model



MLS-MB40401-AI

- 1. 1/2.66"CMOS 4MP,2560x1440@25fp
- 2. Standard Fixed lens 3.6mm
- 3. H.265, H.264, ONVIF protocol
- 4. Dual light source, support full color night vision and infrared night vision
- 5. Built-in microphone and speaker ,Two-way voice intercom
- 6. Six Al alert functions: Area Intrusion, Line-Cross Detection,
- Loitering, Absent Alarm, Vehicle illegal Parking, Vehicle Retrograde (support access to MATE series NVR linkage application)
- 7. DC12V&POE, IR distance up to 20M

(4MP, 6MP, 8MP optional)

MLS-MB42601-AI

- 1. 1/2.7"CMOS 6MP,3072*2048@25fp
- 2. Standard Fixed lens 3.6mm
- 3. H.265, H.264, ONVIF protocol
- 4. Dual light source, support full color night vision and infrared night vision
- 5. Support WDR
- 6. Built-in microphone and speaker ,Two-way voice intercom
- 7. Six Al alert functions: Area Intrusion, Line-Cross Detection,
- Loitering、Absent Alarm、Vehicle illegal Parking、Vehicle Retrograde (support access to MATE series NVR linkage application)
- 8. DC12V&POE, IR distance up to 20M

(4MP, 6MP, 8MP optional)

MLS-MD41601-AI 6MP



- 2. Standard Fixed lens 3.6mm
- 3. H.265, H.264, ONVIF protocol
- 4. Dual light source, support full color night vision and infrared night vision
- 5. Support WDR
- 6. Built-in microphone and speaker ,Two-way voice intercom
- 7. Six Al alert functions: Area Intrusion, Line-Cross Detection,
- Loitering, Absent Alarm, Vehicle illegal Parking, Vehicle Retrograde (support access to MATE series NVR linkage application)
- 8. DC12V&POE, IR distance up to 20M

(4MP, 6MP, 8MP optional)

(4MP, 6MP, 8MP optional)

MLS-MD45801-AI



- 3. H.265, H.264, ONVIF protocol
- 5. Support WDR
- Loitering, Absent Alarm, Vehicle illegal Parking, Vehicle Retrograde
- 8. DC12V&POE, IR distance up to 20M

(4MP, 6MP, 8MP optional)

MLS-MB44401M-AI 4MP



- Standard Motorized lens 2.8-12mm
- 3. H.265, H.264, ONVIF protocol
- 4. Dual light source, support full color night vision and infrared night vision
- 5. Built-in microphone and speaker ,Two-way voice intercom
- 6. Six Al alert functions: Area Intrusion, Line-Cross Detection,
- Loitering、Absent Alarm、Vehicle illegal Parking、Vehicle Retrograde (support access to MATE series NVR linkage application)
- 7. DC12V&POE, IR distance up to 40M

- 1. 1/2.7"CMOS 8MP,3840*2160@25fp
- 2. Standard Fixed lens 3.6mm
- 4. Built-in infrared light, support infrared night vision
- 6. Built-in microphone and speaker ,Two-way voice intercom
- 7. Six Al alert functions: Area Intrusion, Line-Cross Detection,
- (support access to MATE series NVR linkage application)



MLS-MB46401M-AI 4MP

- 1. 1/2.66"CMOS 4MP,2560x1440@25fp
- 2. Standard Motorized lens 2.8-12mm
- 3. H.265, H.264, ONVIF protocol
- 4. Dual light source, support full color night vision and infrared night vision
- 5. Built-in microphone and speaker ,Two-way voice intercom
- 6. Six Al alert functions: Area Intrusion, Line-Cross Detection,
- Loitering、Absent Alarm、Vehicle illegal Parking、Vehicle Retrograde (support access to MATEseries NVR linkage application)
- 7. DC12V&POE, IR distance up to 40M

(4MP, 6MP, 8MP optional)





MATE NVR Series



MLS-NM9104MP MLS-NM9108MP

4CH/8CH

- 1. H.265/H.264 adaptive network camera
- 2. 4CH/8CH POE interface, support up to 16CH 8MP/5MP/4MP/3MP/2MP video input
- 3. 1CH 5MP/4CH Substream Playback
- Mini 1U, 1 SATA interface, 4 PoE/8 PoE(IEEE 802.3at, IEEE 802.3af),1 RJ45
 10M/100M,1HDMI/VGAOutput
- Target Counting, Electronic Fence, Retrograde Detect, Absent Detect (only support private protocol Smart IPC)
- 6. Power Supply: 52V DC



MLS-NM9109M

9CH

- 1. H.265/H.264 adaptive network camera
- 9CH 8MP/5MP/4MP/3MP/2MPvideo input
- 1CH 5MP/4CHSubstreamPlayback
- 4. Mini 1U, 1 SATA interface, 1 RJ45 10M/100M,1HDMI/VGA Output
- Target Counting, ElectronicFence, RetrogradeDetect, Absent Detect (only support private protocol Smart IPC)
- 6. Power Supply: 12V DC



MLS-NM9436R

36CH

- 1. H.265/H.264 adaptive network camera
- 2. 36 CH 4K/5MP/4MP/3MP/2MP video input
- 3. 1CH 4K,4CH 1080P,16CHD1 Playback
- 4. 1.5U, 4 SATA interface, 2 RJ45 10M/100M/1000M,1 HDMI/VGA Output
- 5. Audio in/out 1/1, Alarm in/out 2/1
- Target Counting, Electronic Fence, Retrograde Detect, Absent Detect(only support private protocol Smart IPC)
- 7. Power Supply: 12V DC



MLS-NM9464R

64CH

- H.265/H.264 adaptive network camera
- 2. 64 CH 4K/5MP/4MP/3MP/2MP video input.
- 3. 1CH 4K,4CH 1080P,16CHD1 Playback
- 4. 1.5U, 4 SATA interface, 2 RJ45 10M/100M/1000M,1 HDMI/VGA Output
- 5. Audio in/out 1/1, Alarm in/out 2/1
- Target Counting, Electronic Fence, Retrograde Detect, Absent Detect(only support private protocol Smart IPC)
- Only supports up to 36 split-screen display
 (Note: 64-channel preview needs to be page-turned)
- 8. Power Supply: 12V DC



MLS-NM9216P

MLS-NM9216

16CH

- 1. H.265/H.264 adaptive network camera
- 2. 16CH POE/No POE 4K,25-32CH/5MP/4MP/3MP/2MPvideo input
- 3. 1CH 4K/5MP,4CH1080P Playback
- 1U, 2 SATA interface, 1 RJ45 10M/100M,1HDMI/VGA Output
 No POE: Audio in/out 1/1,Alarm in/out 4/1
- Target Counting, Electronic Fence, Retrograde Detect, Absent Detect (only support private protocol Smart IPC)
- 6. Power Supply: 52V DC



MLS-NM9964R

64CH

- 1. H.265/H.264 adaptive network camera
- 2. 64 CH 4K/5MP/4MP/3MP/2MPvideo input
- 3. 1CH 4K,4CH 1080P,16CHD1 Playback
- 2U, 9 SATA interface, 2 RJ45 10M/100M/1000M,1HDMI/VGA Output
 Audio in/out 1/1.Alarm in/out 2/1
- Target Counting, Electronic Fence, Retrograde Detect, Absent Detect (only support private protocol Smart IPC)
- 7.Only supports up to 36 split-screen display
- (Note: 64-channel preview needs to be page-turned)
- 8. Power Supply: 100-240V AC



MLS-NM9AA8

128CH

- 1. H.265/H.264 adaptive network camera
- 2. 128 CH 4K/5MP/4MP/3MP/2MPvideo input
- 3. 4CH 4K/5MP,16CH1080P Playback
- 4. 3U, 16 SATA interface, 1 RJ45 10M/100M/1000M,1HDMI/VGA Output
- 5. Audio in/out 1/1, Alarm in/out 4/4
- Target Counting, Electronic Fence, Retrograde Detect, Absent Detect
 (only support private protocol Smart IPC)
- 7. Support RAID0, RAID1,RAID5,RAID6,RAID10; Power Supply: 100-240V AC



MLS-NM99A8

128CH

- 1. H.265/H.264 adaptive network camera
- 2. 128 CH 4K/5MP/4MP/3MP/2MPvideo input
- 3. 4CH 4K/5MP,16CH1080P Playback
- 4. 2U, 9 SATA interface, 1 RJ45 10M/100M/1000M,1HDMI/VGA Output
- 5. Audio in/out 1/1, Alarm in/out 4/4
- Target Counting, Electronic Fence, Retrograde Detect, Absent Detect (only support private protocol Smart IPC)
- 7. Support RAID0, RAID1,RAID5,RAID6,RAID10; Power Supply:100-240V AC

Solar Powered 4G Router & Solar Powered WIFI Repeater

Model MLS-SR1 Solar Powered 4G Router

- 1. 15w solar panel +20000mAh battery works stably
- 2. It can work for 5~7 days in rainy weather after full charge
- 3. Built-in 4G network module (Cat.4), DL 150Mbps, UL 50Mbps
- 4. 4G band support for European version and US version is optional
- 5. 2.4G WIFI,802.11b/g/n, up to 150Mbps
- 6. Supports a maximum of 8 devices to be added to the network
- 7. wifi radiation distance in open areas can reach 30~50 meters
- 8. PVC+EVA+tempered glass, IP66
- 9. Power input: DC5V

Plug and play, easy to install

No need for network cables and power supply







Model MLS-SR20 Solar Powered WIFI Repeate

- 1. 15w solar panel +20000mAh battery works stably
- 2. It can work for 5~7 days in rainy weather after full charge
- 3. Access the Internet via a wireless connection to a wifi router
- 4. 2.4G WIFI,802.11b/g/n, up to 300Mbps
- 5. Supports a maximum of 15 devices to be added to the network
- 6. wifi radiation distance in open areas can reach 50~150 meters
- 7. PVC+EVA+tempered glass, IP66

WiFi radiation distance can reach 50-150 meters

wifi radiation distance in open areas can reach 50~150 meters

8. Power input: DC5V







